

COILED TUBING REEL

OVERVIEW

The DWELLOP Reel systems have for more than 20 years proven their durability and shown resilience in harsh operating conditions from around the world. The latest upgrade now allows the Reels to run up to 150-ton spools, with triple motor redundancy.




KEY NUMBERS

- ❖ SWL 150 tons
- ❖ 70 Nm spool torque
- ❖ 500 ft/h spooling capacity
- ❖ Fits Drop In Drum spools and shipping spools
- ❖ Spool size: 250in

CLASS LEADING WORKING ENVIROMENT

CLASS LEADING RIG-UP EFFICIENCY

CLASS LEADING OPERATIONAL EFFICIENCY



KOPPHOLEN 25

4313 SANDNES

NORWAY



+47 51 57 28 00



SALES@DWELLOP.NO


COILED TUBING REEL

TECHNICAL

- ❖ Hydraulic foldable Level Wind Platform
- ❖ Hydraulic foldable Camera Arm
- ❖ Spool jacks for Drop In Drum Cradles
- ❖ Harsh environment proven
- ❖ Gearbox access platform
- ❖ HP swivel access platform
- ❖ Low maintenance
- ❖ Level Wind ladder

OPTIONS

- ❖ Adjustable Levelwind staircase
- ❖ Inhibitor fluid system
- ❖ Tubing clamp on Counter Head
- ❖ Stainless steel fittings
- ❖ Hydraulic operated
Camera Arm
- ❖ Triple motor
Gearbox



KOPPHOLEN 25

4313 SANDNES

NORWAY



+47 51 57 28 00



SALES@DWELLOP.NO